

Avery Dennison[®] MPI 2120 Matte

Permanent / Removable StaFlat™

(formerly: MPI 2010)

Revision: 5 Dated: 04/11/16

Uses:

Avery Dennison MPI 2120 Matte film is a flexible calendared vinyl film. MPI 2120 offers exceptional value for applications requiring premium calendared film durability combined with a permanent or removable adhesive performance.



Face: 3.4 mil (86 microns) matte calendared



Adhesive: Clear Acrylic



Liner: 90# StaFlat™



Durability: Up to 6 years (unprinted)

Application Surfaces:

Flat, simple curves (restricted to non-spill areas)

Features:

- 100% opacity, completely covers whatever is underneath
- Matte finish
- Outstanding durability and outdoor performance
- Great image clarity and color pop
- Dimensionally stable liner for easy converting
- ICC profiles available on Avery Dennison's website (<https://avery-us.color-base.com>)
- ASTM E84 Class 1 or A rating

Conversion:

- Solvent based inkjet
- UV inkjet
- Latex Inkjet
- Mild/Eco Solvent inkjet

Common Applications:

- Fleet
- POP/ Tradeshow
- Floor Graphics
- Wall Murals
- Outdoor Signage

Product Data Sheet

Page 1 of 3



Graphics
Solutions

graphics.averydennison.com
Customer Service: 800-282-8379

Avery Dennison[®] MPI 2120 Matte

Permanent / Removable StaFlat™

(formerly: MPI 2010)

Revision: 5 Dated: 04/11/16

Physical Characteristics:

Property		Value
Caliper, face		3.4 mil (86µm)
Caliper, adhesive		1.0mil (25 µm)
Dimensional stability		<0.065"(1.651 mm)
		Note: Ink loads in excess of 250% may cause increased shrinkage of the printed film.
Tensile at Yield		
Elongation		
Gloss	Hunter Gloss @ 60	<16
Adhesion: 15 min.	Permanent	4.7 lbs/in (831 N/m)
Removability		Permanent
Flammability	ASTM E84 Class 1 or A rating	Self Extinguishing
Shelf-Life		2 years from date of manufacture when stored at the following temperatures and humidity conditions 68°-77° F (20° - 25° C) and 50±5% R. H.
Durability	Vertical Exposure	Unprinted – 6 years Printed – Up to 5 years
Min. Application Temperature		50° F (10° C)
Service Temperature		-50° to 180° F (-45° to 82° C) (Reasonable range of temperatures which would be expected under normal environmental conditions).
Chemical resistance		Resistant to most mild acids, alkalis, and salt solutions.

Data represents average values where applicable, and is not intended for specification purposes.

Warranty:

This Warranty applies to the Product listed in this Data Sheet. All statements, technical information (including physical and chemical characteristics) and recommendations about Avery Dennison products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold subject to the Purchaser's assent and agreement that Purchaser is responsible for, and has independently determined, the suitability of such products for its purposes or its customer's purposes. Avery Dennison products are warranted to be free from defects in material and workmanship (i) for two years from the date of manufacture, or (ii) from the date of manufacture until the expiration of the period stated on the specific Product Data Sheet in effect at the time of delivery. Such time periods are subject in either case to the proper storing and application of said product, and the failure to properly store or apply the product, including without limitation the failure to follow any applicable Instructional Bulletin, negates any warranty. It is expressly agreed and understood that Avery Dennison's sole obligation and Purchaser's exclusive remedy under this warranty, under any other warranty, express or implied, or otherwise, shall be limited exclusively to: (a) repair or replacement of defective product without charge at Avery Dennison's plant or at the location of the product (at Avery Dennison's election), or (b) in the event repair or replacement are not commercially practical, a credit amount up to the price of the product taking into account the defect in the product in Avery Dennison's sole discretion.

THE WARRANTY EXPRESSLY SET FORTH ABOVE IS IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR USE AND/OR NON-INFRINGEMENT. SELLER SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND MANUALLY SIGNED BY AN OFFICER OF AVERY DENNISON.

AVERY DENNISON'S LIABILITY FOR DEFECTIVE PRODUCTS SHALL NOT EXCEED THE PURCHASE PRICE PAID THEREFORE BY PURCHASER AND IN NO EVENT SHALL AVERY DENNISON BE RESPONSIBLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES WHETHER FORESEEABLE OR NOT, CAUSED BY DEFECTS IN SUCH PRODUCT, WHETHER SUCH DAMAGE OCCURS OR IS DISCOVERED BEFORE OR AFTER REPLACEMENT OR CREDIT, AND WHETHER OR NOT SUCH DAMAGE IS CAUSED BY AVERY DENNISON'S NEGLIGENCE.

All sales and contracts for sale of Products are subject to Purchaser's assent and agreement to this Warranty. Avery Dennison hereby objects to any terms or conditions contained in any purchase order or other communication of any kind from the Purchaser that is conflicting, inconsistent or additional to this Agreement.

Product Data Sheet

Page 2 of 3



Graphics Solutions

graphics.averydennison.com
Customer Service: 800-282-8379

Avery Dennison[®] MPI 2120 Matte

Permanent / Removable StaFlat™

(formerly: MPI 2010)

Revision: 5 Dated: 04/11/16

Removability:

Avery Dennison does not guarantee removability from the following substrates:

- Surfaces with poor paint-to-substrate adhesion
- Wallboard
- Existing graphics that must remain intact; damage to existing graphic when film is removed
- Aged paint or metal that may have surface oxidation or chalking
- Outdoor, horizontal surfaces

Revisions are italicized

Avery Dennison is a registered trademark of Avery Dennison Corporation

Product Data Sheet

Page 3 of 3



Graphics
Solutions

graphics.averydennison.com
Customer Service: 800-282-8379